





Block Lift for shipbuilding

This equipment is for fine adjustment of blocks mounted close to the shipyard dock & Pre-erection yard and for assembly of welded seam joints.

Block lifter is able to adjust fine control to frames at +- 1mm and let frame synchronized movment for 4 or 8 block lifters.

SAMHOON is providing control with monitor screen in order to keep checking center of gravit, horizontal and heigt in real time.



- 1. Front wheel
- 2. Electronic panel
- 3. Rear wheel
- 4. Oil tank
- 5. Vertical cylinder
- 6. Horizontal cylinder
- 7. Electronic wire wheel
- 8. Main conector

Specification

| Model | Lifting specification | | Working pressure | Horizontal Shifting | Height |
|----------|-----------------------|------------|---------------------|------------------------|--------|
| | Capacity (ton) | Stroke(mm) | (bar) | (mm) | (mm) |
| SHBL-100 | 100 | 300 | 210 | 250 | 1800 |
| SHBL-200 | 200 | 300 | 210 | 250 | 1800 |
| SHBL-300 | 300 | 300 | 210 | 250 | 1800 |
| SHBL-400 | 400 | 300 | 300 | 250 | 1800 |
| SHBL-500 | 500 | 300 | 300 | 250 | 1800 |

Controller







<Wireless controller>



<Cable reel cart>














Features



Entire display

- Hydraulic temperature
- Hydraulic pressue
- Current location and cylinder speed



Hight control

- Individual hydraulic pressue
- current hight of machine
- Control hight as group A and B



Fine adjustment

- Detail location of machine
- Fine adjustment at -+ 1mm
- Control hight and vertical location



Center of gravity display

- Detail C.O.G of all machine
- Checking it in real time
- Display as group or entire machine

Contact Us

SAMHOON CO., LTD.

Head Office: 121, Hallim-ro, Hallim-myeon, Gimhae-si, Gyeongsangnam-do, Korea Factory: 33, Myengdog-ro, Hallim-myeon, Gimhae-si, Gyeongsangnam-do, Korea

TEL: +82-55-343-1219 FAX: +82-55-345-1012

E-MAI: : sam_hoon@nate.com



Impossible ? I'm possible !